


### ■ HPD13/L

#### Features 特点

- The optimal design realizes high quality sound and low distortion.  
高音质、低失真最佳设计
- Compact size using flat wire.  
扁平线小尺寸封装
- Low radiation noise by magnetically shielded construction  
闭合磁路封装，低辐射
- High current, Low resistance.  
大电流，低电阻
- Operating temperature : -40°C~+125°C.  
工作温度：-40°C~+125°C



#### Applications 应用

- Suitable as choke for digital amp. Car audio, LCD and PDP TV, 5.1ch Home theater, etc.  
适用于数字功放扼流。如汽车音响，LCD 电视和 PDP 电视，5.1 声道家庭影院等

#### Electrical characteristics 电气性能

Part number 料号	Inductance 电感量 $\mu\text{H} \pm 10\%$	DCR 直流电阻 $\text{m}\Omega$		Isat 直流饱和电流 A (typical)			Irms 温升电流 A (typical)	
		typ	max	10%drop	20%drop	30%drop	20°Crise	40°Crise
HPD13-472KT	4.7	4.5	5.4	15.5	16.8	17.2	8	11.9
HPD13L-103KT	10	4.5	5.4	5.9	6.5	6.9	8	11.9
HPD13-103KT	10	8.4	10.5	9.8	11	11.3	6	9.5


#### Remark

- ① Inductance is measured with a LCR meter Agilent 4284A or equivalent.  
Test frequency at 100kHz
- ② DC resistance is measured with Keithley 580 Milliohm Meter, or equivalent.  
Reference ambient temperature 25°C
- ③ SRF measured using an Agilent 4395A network analyzer and an Agilent 16193A test fixture.
- ④ DC current at 25°C that causes the specified Inductance drop from its value without current.
- ⑤ Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
- ⑥ Electrical specifications at 25°C

#### 备注

- ① 电感量测试采用 Agilent 4284A 数字电桥或同等仪器；  
测试频率 100KHz
- ② 直流电阻测试采用 Keithley 580 毫欧表或同等仪器；  
环境温度 25° C
- ③ SRF 使用 Agilent 4395A 网络分析仪和 Agilent 16193A 测试夹具测量。
- ④ 直流电流在 25° C，加载导致指定电感从没有电流的值下降。
- ⑤ 导致指定温度从 25° C 环境温度上升的电流。此信息仅供参考，不代表绝对最大额定值。
- ⑥ 25° C 时的电气规格

### Dimensions 结构尺寸



### Electrical Characteristic Curve

